





DIMENSIONS & WEIGHT		25-seater	29-seater	33-seater
Overall Length / Width / Height	(mm)	6,245 / 2,010 / 2,630	6,990 / 2,010 / 2,630	7,730 / 2,010 / 2,630
Wheelbase	(mm)	3,490	3,995	4,550
Wheel Tread (Front / Rear)	(mm)	1,655 / 1,495		
Min. Ground Clearance	(mm)	190		
Interior Length / Width / Height	(mm)	5,480 / 1,845 / 1,860	6,225 / 1,845 / 1,860	6,970 / 1,845 / 1,860
Front / Rear Overhang (F.O.H. / R.O.H.)	(mm)	940 / 1,800	940 / 2,040	940 / 2,225
Curb Weight	(kg)	3,520	3,685	3,955
GVW	(kg)	5,200	5,600	6,100



ENGINE		25-seater	29-seater	33-seater
Model		4M50-5AT5		
Type		4-Stroke Direct Injection Diesel with Turbocharger and Water Intercooler		
Cylinders		In-line 4		
Displacement	(cc)	4,899		
Compression Ratio		15.5:1		
Bore x Stroke	(mm)	114 x 120		
Max. Power	(Ps / rpm)	179 / 2,700		
Max. Torque	(N-m / rpm)	530 / 1,600		
Fuel Tank Capacity	(L)	100		



TRANSMISSION		25-seater	29-seater	33-seater
Type		6 Forward and 1 Reverse M/T (Synchronesh)		
Gear Ratios	1st		5.175	
	2nd		2.913	
	3rd		1.682	
	4th		1.000	
	5th		0.793	
	6th		0.669	
	Reverse		5.175	
Final Gear Ratio			4.875	



AXLE		25-seater	29-seater	33-seater
Front / Rear		Reverse Elliot "I" Beam / Fully Floating		
BODY & SUSPENSION				
Body Type		Semi-Integral (Monocoque)		
Front		Parabolic Laminated Leaf Spring with Shock Absorber and Stabilizer		
Rear		Parabolic Laminated Leaf Spring with Shock Absorber		
BRAKE				
Service		Drum Brake with Manual Adjuster (Front and Rear), Hydraulic with Vacuum Servo Assistance		
Parking		Internal Expanding Type at Rear Side of Transmission		
Auxiliary		Exhaust Brake		



TIRE & WHEEL		25-seater	29-seater	33-seater
Tire (Single / Dual)		Single 7.00 R16-10 PRLT / Dual 7.00 R16-8PRLT		
Wheel		16 x 5.50		
STEERING				
Gear Type		Ball and Nut Type with Integral-type Hydraulic Power Booster		
Power Steering		Equipped		
SAFETY				
		3 pt. ELR x2 and 2 pt. Lapbelt x3, Reverse Warning Buzzer		
ELECTRICAL SYSTEM				
Battery		12V (x2)		



Photos and specifications may vary from actual unit. Sojitz Fuso Philippines reserves the right to change specifications without prior notice.



FUSO authorized distributor
SOJITZ FUSO PHILIPPINES CORPORATION
www.fuso.com.ph

Brochure part no.: B010101



SOJITZ FUSO PHILIPPINES CORPORATION

ROSA



Powered by a 4.9L Turbo Direct Injection Diesel

Available in • 25-seater (Standard) • 29-seater (Deluxe) • 33-seater (Grand)



Rear luggage area

Cockpit and ergonomics



The Rosa features a driver-centric dashboard layout with car-like features



High-contrast meter cluster



Tilt adjustable steering wheel with collapsible steering column

Passenger comfort



Spacious and relaxing interior with individually reclining seats for each passenger



Ample legroom



Automatic passenger door